

i.MX 8X FAMILY OF APPLICATIONS PROCESSORS

Built with a high-level integration to support graphics, video, image processing, audio, and voice functions, the i.MX 8X processor family is ideal for safetycertifiable and efficient performance requirements. Applications for the i.MX 8X processor include industrial automation, HMI, industrial control, robotics, building control, automotive cluster, display audio infotainment, and telematics applications.

TARGET APPLICATIONS

- Automotive—instrument cluster, infotainment, display audio, rear seat entertainment, smart antenna, Vehicle-to-Vehicle (V2X), gateway and camera systems
- Industrial vehicle—avionics cockpit display, in-flight entertainment, train and heavy equipment HMI
- Advanced industrial human machine interface (HMI) and control—PLC, I/O controller, home/building control
- Robotics—drone, mobile service robot
- Building Control—fire and security panel, elevator control, HVAC control
- Healthcare—patient monitor
- Networking—specialty gateway, low-end video conference terminal
- Mobile payment—payment systems
- General-purpose HMI solutions

SAFEGUARD MISSION CRITICAL DISPLAYS AND CONTROL FUNCTIONS

 Increase your system's accuracy—The i.MX 8X processor with optional Error Correcting Code (ECC) is the first i.MX product to support applications such as programmable logic controller (PLC), input/output (I/O) controller, robotic control and drones.



- Secure your system with advanced programmable security—Ensure top-of-the-line security from first boot to securing with the latest cryptography standards (AES, flashless SHE, elliptical curve cryptography, key storage).
- Improve your system reliability with Fully Depleted Silicon on Insulator (FD-SOI)—built using 28 nm FD-SOI, the i.MX 8X applications processor dramatically improves mean time between failures (MTBF) and reduces latch-ups due to FD-SOI's inherently high immunity to soft errors.
- Offload time-critical tasks—Utilize the Arm[®] Cortex[®]-M4F core for time-critical tasks such as backup camera display, audio control and general system monitoring and wakeup.

ADVANCED INTEGRATION

- Multi-domain voice recognition—Utilize the Cortex-A35 and Cortex-M4F cores as well as the Tensilica® HiFi 4 DSP for audio pre- and post- processing, key word detection and speech recognition for hands-off interaction. Take advantage of the large library of HiFi optimized audio and voice codecs and audio enhancement software packages.
- Three screens of independent content—Develop innovative, multi-screen platforms through the ability to drive up to two 1080p screens, MIPI-DSI or LVDS, and one parallel WVGA display with independent content to reduce system cost.

• Flexible memory options—Offers LP-DDR4 memory interface for high performance and low standby power, or DDR3L interfaces for lowest system cost. For fast boot from SPI NOR flash, two Quad SPI or one Octal SPI are available as well as support for SD 3.0, eMMC 5.1 and RAW NAND.

LOW-POWER OPTIMIZED PERFORMANCE

- Up to four (4) 1.2 GHz Cortex-A35 processors—A powerful and powerefficient upgrade path for nextgeneration solutions. The Cortex-A35 is Arm's most efficient Armv8 core.
- Multiple systems, one processor— Delivers a high level of integration on one chip, such as the Cortex-A35 applications core, Cortex-M4F realtime processing core, hardware accelerated graphics and video, high performance DSP, and more.
- **Optimized power**—Reduce thermal system cost and power usage by shutting down the Cortex-A35 core while the Cortex-M4F core remains active to perform low-level system monitoring tasks.

THE SCALABLE PLATFORM OF CHOICE

NXP developed this highly scalable product family to provide a muchneeded migration path for next generation devices. The Cortex-A35 provides full Armv8-A 64-bit support while maintaining seamless backwards compatibility with 32-bit Armv7-A software. The i.MX 8 series continues to build on the industry leading scalability of the i.MX product line. Easily transition between the i.MX 8 family and the i.MX 8X family with its high level of software and hardware reuse across the full range of product capabilities.

- Comprehensive software support Android[™], Linux[®], QNX, Green Hills[®], FreeRTOS[™] and partner commercial operating systems
- Automotive Auto (-40 °C to 125 °C Tj)
- Industrial Industrial (-40 °C to 105 °C Tj)
- Consumer qualified Consumer (-20 °C to 105 °C Tj)

PIN AND POWER COMPATIBLE

Highly scalable design options allow a single platform to cover multiple products. Pin- and power-compatible packages (in 0.8 pitch) allow for a single PCB platform and different i.MX 8X processors as product needs dictate.

PRODUCT LONGEVITY

When designing with i.MX, you can depend on the quality of the product and the stable, consistent supply of product for your embedded designs through the NXP Product Longevity program.

Visit <u>www.nxp.com/productlongevity</u> for details.

i.MX ECOSYSTEM ALLIANCES

Leveraging the broad Arm community, the i.MX product line builds technology alliances to enable better customer solutions and faster time-to-market. Solutions include:

- Tool chains
- Software
- Codecs
- Middleware/applications
- Embedded board solutions
- System integrators
- Training

i.MX 8X FAMILY— DIFFERENTIATED FEATURES

Feature	i.MX 8DualXPlus/ i.MX 8QuadXPlus	i.MX 8DualX	
Arm [®] Core	2 x Cortex-A35 (i.MX 8DualXPlus) 4 x Cortex-A35 (i.MX 8QuadXPlus)	2 x Cortex-A35	
Arm Core	1 x Cortex-M4F	1 x Cortex-M4F	
DSP Core	Tensilica® HiFi 4 DSP	Tensilica HiFi 4 DSP	
DRAM	32-bit DDR3L (ECC option)/ LPDDR4 (no ECC)	16-bit DDR3L\ LPDDR4 (no ECC)	
GPU	1 x GC7000Lite Performance Optimized	1 x GC7000Lite Power Optimized	
VPU	4K h.265 dec, 1080p h.264 enc/dec	1080p h.264 enc/ dec	
Ethernet	2 x Gigabit with AVB	1 x Gigabit with AVB 1 x 10/100	
USB with PHY	1 x USB 3.0 (can be used as USB 2.0) 1 x USB 2.0	2 x USB 2.0	

i.MX 8X FAMILY BLOCK DIAGRAM

Core Complex 1	Core Complex 2		Connectivity
2-4 x Arm® Cortex®-A35	Cortex-M4F	1 x I ² C	4 x UART
	16 KB I-cache	1 x UART	
32 KB I-cache 32 KB D-cache	16 KB D-cache	6 x GPIO	8 x I ² C
512 KB L2 cache with ECC	256 KB SRAM	1 x TPM Timer	4 x SPI
Multimedia	Memo	ory	1 or 2 x 1 Gbit Ethernet AVB
GPU 1 x 4-Shader, OpenGL® ES 3.0 or 3.1,	DDR3L @ 933 MH LPDDR4 @ 1200		1 x 10/100 Ethernet
Vulkan® VPU	2 x SDIO3.0/		3.3 V/1.8 V GPIO
Video: h.265 dec 4K, h.264 enc/dec 1080p	RAW NANE 2 x Quad/1 x		PCIe 3.0 with L1 Substate-1-lane
Audio	2 x Quad/1 x		1 x USB3 OTG w/PHY
DSP Core	Secu	rity	1 or 2 x USB2 OTG w/PHY
Tensilica® HiFi 4 32 KB I 48 KB D	HAB, SRTC, SJT.	AG, TrustZone®	TOF2 X USB2 OTG W/PHT
512 KB SRAM (448 KB OCRAM, 64 KB of TCM)	AES256, RSA40	096, SHA-256	3 x CAN/CAN FD
	3DES, ARC	C4, MD-5	MOST 25/50
Display and Camera I/O	Flashless SHE, ECC		
Display Processor with SafeAssure®	Tamper, Inline	Enc Engine	4 x 4 Keypad
	System 0	Control	4 x PWM
2 x MIPI-DSI/LVDS Combo PHY*	Power Control, 0	Clocks, Reset	1 x ADC (6-ch.)
1 x Parallel Display 1 x Parallel CSI	BootR		2 x ASRC, SPDIF
	PMIC interface (dedicated I ² C)	
1 x MIPI CSI	Domain Resource	e Partitioning	4 x SAI, ESAI, MQS

Available on certain product families Note: Accessing muxable controller's full capabilities is dependent upon board component choices

www.nxp.com/iMX8X

NXP, the NXP logo and SafeAssure are trademarks of NXP B.V. All other product or service names are the property of their respective owners. Arm, Cortex and TrustZone are registered trademarks of Arm Limited (or its subsidiaries) in the EU and/or elsewhere. All rights reserved. © 2021 NXP B.V.