

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	A	ORIGINAL RELEASE	11-27-14	G. R. R. M. C
	A1	315-79544 FOOTPRINT UPDATE	12-03-14	G. R. R. M. C
	B	Re-SPIN Per ECO56843	03-07-15	G. R. R. M. C

NOTES (UNLESS OTHERWISE SPECIFIED):

1. THIS DRAWING SPECIFIES THE REQUIREMENTS FOR A PRINTED WIRING BOARD IN ACCORDANCE WITH SPECIFICATION IPC-A-600 CLASS 2 (LATEST REVISION).

2. THE PWB MUST BE LEAD FREE ASSEMBLY PROCESS COMPATIBLE AND MUST BE ABLE TO HANDLE A MINIMUM OF 5 CYCLES AT 260 DEGREES CELSIUS FOR 10 SECONDS.

3. BASE MATERIAL - LAMINATE AND PREPREG SHALL MEET IPC-4101B-26, 83 or 98
T_g - MUST BE GREATER THAN OR EQUAL TO 150 DEGREES CELSIUS.
T_d - MUST BE GREATER THAN OR EQUAL TO 330 DEGREES CELSIUS.

4. COPPER FOIL WEIGHT - SEE STACKUP DETAIL 'A'

5. CHARACTERISTIC IMPEDANCE - NONE

6. MINIMUM CONDUCTIVE WIDTH/SPACING TO BE .004"/.004"

7. PLATING FINISH - BOTH SIDES ENIG (ELECTROLESS NICKEL IMMERSION GOLD):
.05080-.232 MICRON (2-8 MICROINCH) OF GOLD OVER
2.540-6.350 MICRON (100-250 MICROINCH) OF NICKEL.

8. ALL THROUGH HOLE VIAS MAY BE PLATED SHUT.

9. SOLDERMASK - BLACK COLOR (TAIYO OR EQUIVALENT), BOTH SIDES.
MODIFICATION OF SOLDERMASK IS NOT ALLOWED WITHOUT WRITTEN PERMISSION FROM FREESCALE.

10. SILKSCREEN - WHITE EPOXY INK, BOTH SIDES. NO SILK ON PADS.

11. ELECTRICAL TEST - 100% IPCD356.

12. PRINTED WIRING BOARD IS TO BE INDIVIDUALLY BAGGED.

13. DRC'S MUST BE RUN ON THE GERBER BEFORE BUILDING BOARDS, UNLESS PRIOR APPROVAL IS GIVEN IN WRITING BY FREESCALE.

14. TEARDROPS MAYBE ADDED AT THE FAB HOUSE TO ALL SIGNAL LAYERS.

15. TWO SOLDER SAMPLES TO BE PROVIDED.

16. BASIC GRID INCREMENT AT 1:1 IS .0001.

17. SUPPLIER MARKINGS - ON SOLDER SIDE ONLY, WHERE SHOWN.
- MUST BE UL RECOGNIZED AND MUST HAVE AN ID THAT CONFORMS TO UL94V-0


18. THE PWB WILL BE MARKED AS LEAD FREE BY USE OF AN INK STAMP (Pb)

19. THE PWB WILL BE MARKED AS LEAD FREE PROCESS COMPATIBLE BY USE OF AN INK STAMP (260°C)



20. ALL PLATED AND NON-PLATED THROUGH HOLES ARE TO BE DRILLED AT PRIMARY DRILL STEP.
ALL HOLE LOCATION TOLERANCES ARE TO BE $\pm .002$ IN REFERENCE TO THE PRIMARY DATUM.

21. FINISHED PCB MUST BE PANELIZED FOR ASSEMBLY ACCORDING TO CONTRACT MANUFACTURERS REQUIREMENTS. THE ADDITION OF RAILS AND .125"NON-PLATED TOOLING HOLES ARE AT THE DISCRETION OF CONTRACT MANUFACTURER. PANELIZATION MUST BE APPROVED BY CONTRACT MANUFACTURER.

- 22 THIS BOARD USES VIA-IN-PAD:
A. VIA-IN-PAD TO BE FILLED WITH NON-CONDUCTIVE VIA FILL.
LACKWERKE-PETERS PP2795 OR EQUIVALENT AND MADE PLANAR TO THE PADS.
B. OVERPLATE THE FILLED VIA AND APPLY FINISH METAL TREATMENT.



.062" THICK +/-10%

DRILL CHART: TOP to BOTTOM					
ALL UNITS ARE IN MILS					
	FIGURE	SIZE	TOLERANCE	PLATED	QTY
22		5.0	+0.0/-5.0	PLATED	14
8	.	10.0	+0.0/-10.0	PLATED	156
22		10.0	+0.0/-10.0	PLATED	21
	o	40.0	+3.0/-3.0	PLATED	103
	o	52.0	+3.0/-3.0	PLATED	5
	o	36.0	+2.0/-2.0	NON-PLATED	2
	Δ	125.0	+2.0/-2.0	NON-PLATED	4

FINISHED Cu WEIGHT

	LAYER 1	COMPONENT SIDE	1/2 oz.
	LAYER 2	GROUND PLANE	1 oz.
	LAYER 3	INTERNAL_1	1 oz.
	LAYER 4	SOLDER SIDE	1/2 oz.

DETAIL A
LAYER STACKUP
SCALE: NONE

PART NO. 170-28660		FREESCALE			
--- PUBI (PUBLIC INFORMATION) <input checked="" type="checkbox"/> FIVU (FREESCALE INTERNAL USE ONLY) --- FCP (FREESCALE CONFIDENTIAL PROPRIETARY)		THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO FREESCALE AND SHALL NOT BE USED FOR ENGINEERING DESIGN PROCUREMENT OR MANUFACTURE IN WHOLE OR IN PART WITHOUT THE CONSENT OF FREESCALE.			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: .XX .01 ANGLES .XXX .005 -0.30° <input checked="" type="checkbox"/> RMS ALL MACHINED SURFACES BREAK ALL SHARP EDGES AND CORNERS. REMOVE BURRS. UNDERLINE DIM. NOT TO SCALE. THIRD ANGLE ORTHOGRAPHIC PROJECTION IS USED.		APPROVALS DRAWN neuronPro-RCC02C CHECKED GONZALEZ R.R.M.C DESIGN ENGINEER BILL SMITH		DATE 03-07-15 03-07-15 03-07-15	
		TITLE: 6501 WILLIAM CANNON DRIVE WEST AUSTIN, TEXAS 78735 USA PRINTED WIRING BOARD FRDM-BC3770-EVB			
		SIZE D	CAD FILE NAME LAY-28660	DWG. NO. FAB-28660	REV B
		SCALE 1/1 DO NOT SCALE DRAWING		SHEET 1 OF 1	