

MRF1K50H 230 MHz PRODUCTION TEST FIXTURE

ORDERABLE PART NUMBER: **MRF1K50H-TF4**



PUBLIC



SECURE CONNECTIONS
FOR A SMARTER WORLD

License




- Open and read the License.pdf included in the same zip file as the document you are currently reading. By using the documentation materials included in this zip file, you indicate that you accept the terms of the agreement.

Introduction



- The NXP MRF1K50H is a 1.8-500 MHz, 1500 W CW RF power LDMOS transistor housed in an NI-1230 air-cavity ceramic package. Its unmatched input and output allows wide frequency range utilization.
 - Further details about the device, including its data sheet, are available [here](#).
- The following pages describe the 230 MHz pulse test fixture.
- The test fixture can be ordered through NXP's distribution partners and etailers using part number MRF1K50H-TF4.



Fixture Overview – PCB 10.16 cm x 15.24 cm (4.0" x 6.0")



Typical Pulse Performance




Typical Performance (P1dB): $V_{DD} = 50\text{ Vdc}$, $I_{DQ(A+B)} = 100\text{ mA}$, $P_{in} = 1.3\text{ W}$ (31.1 dBm), Pulse

Frequency (MHz)	Output Power (W)	Signal Type	Power Gain (dB)	Drain Efficiency (%)
230	1500 Peak	Pulse (100 μs , 20% Duty Cycle)	23.7	74.0




Quick Start

1. Mount the reference circuit onto a heatsink capable of dissipating more than 140 W in order to provide enough thermal dissipation (the circuit is capable for more but has been measured in pulse conditions).
2. Connect the ground.
3. Terminate the RF output with a 50 ohm load capable of handling more than 1500 W peak power.
4. Connect the RF input to a 50 ohm source with the RF off.
5. Connect the gate voltage, set to 0 V.
6. Connect the drain voltage (V_{DD}) and raise them slowly to 50 V. Current should be 0 A.
7. Raise the gate voltage slowly until the drain current reaches the desired level (drain quiescent current $I_{DQ(A+B)} = 100$ mA typically). The gate voltage should be around 2.4 V.
8. Set the RF input to pulse conditions (100 μ s pulse width with 20% duty cycle).
9. Raise the RF input slowly to 1.3 W (31.1 dBm).
10. Check the RF output power (typically 1500 W peak), the drain current (around 9 A peak for this power level) and the temperature of the board.



Component Placement Reference




*C4, C18, C19, C20, C21, C22, and C23 are mounted vertically.

Bill of Materials

Part	Description	Part Number	Manufacturer
C1, C2, C3	22 pF Chip Capacitors	ATC100B220JT500XT	ATC
C4	27 pF Chip Capacitor	ATC100B270JT500XT	ATC
C5, C6	22 μ F, 35 V Tantalum Capacitors	T491X226K035AT	Kemet
C7, C9	0.1 μ F Chip Capacitors	C1210C104K5RACTU	Kemet
C8, C10	220 nF Chip Capacitors	C1812C224K5RACTU	Kemet
C11, C12, C25, C26	1000 pF Chip Capacitors	ATC100B102JT50XT	ATC
C13	51 pF Chip Capacitor	ATC800R510JT500XT	ATC
C14	24 pF Chip Capacitor	ATC800R240JT500XT	ATC
C15, C16, C17	20 pF Chip Capacitors	ATC800R200JT500XT	ATC
C18, C19, C20, C21, C22, C23	240 pF Chip Capacitors	ATC100B241JT200XT	ATC
C24	8.2 pF Chip Capacitor	ATC100B8R2CT500XT	ATC
C27, C28, C29, C30, C31, C32	470 μ F, 63 V Electrolytic Capacitors	MCGPR63V477M13X26-RH	Multicomp
Coax1, 2, 3, 4	25 Ω Semi Rigid Coax, 2.2" Shield Length	UT-141C-25	Micro-Coax
L1, L2	5 nH Inductors	A02TKLC	Coilcraft
L3, L4	6.6 nH Inductors	GA3093-ALC	Coilcraft
R1, R2	10 Ω , 1/4 W Chip Resistors	CRCW120610R0JNEA	Vishay
PCB	Arlon AD255A 0.030", $\epsilon_r = 2.55$	D80474	MTL

Tuning Tips

- Moving C4 to the left reduces IRL and increases gain.
- Moving C13 to the right increases efficiency but decreases output power and gain.
- Moving C14-C17 to the right also increases efficiency but decreases output power and gain.
- The distance between C13 and C14-C17 is varied to achieve desired trade-off between output power and efficiency.




*C4, C18, C19, C20, C21, C22, and C23 are mounted vertically.

Impedances

f MHz	Z_{source} Ω	Z_{load} Ω
230	$1.4 + j2.8$	$2.2 + j1.7$

Z_{source} = Test circuit impedance as measured from gate to gate, balanced configuration.

Z_{load} = Test circuit impedance as measured from drain to drain, balanced configuration.



Revision History

- The following table summarizes revisions to the content of the MRF1K50H 230 MHz Test Fixture zip file.

Revision	Date	Description
0	September 2019	• Initial Release



SECURE CONNECTIONS
FOR A SMARTER WORLD